

Application Serial No: 10/518,136

Responsive to the Advisory Action of 8/6/2008 and the final Office Action of 4/7/2008

RECEIVED
CENTRAL FAX CENTER
SEP 05 2008**IN THE CLAIMS****Amendments To The Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-2. (Cancelled)

3. (Currently Amended) A ~~fluorometer system~~ for detecting intensity of fluorescence generated from a substance that is excited by light ~~emitted from a light source~~, comprising:

a single light source emitting light having one wavelength;

a fluorometer, comprising:

n (n is an integer of not less than 2) narrow-band-pass filters for transmitting light in different limited wavelength regions of the fluorescence, and
n light-receiving portions having one-to-one correspondence with the n narrow-band-pass filters,

wherein the n narrow-band-pass filters are arranged to each have a different incident angle of light,

wherein the n narrow-band-pass filters share a similar transmittance configuration;

wherein an intensity P1 of fluorescence transmitted through a first narrow-band-pass filter is detected by a first light-receiving portion, and

wherein fluorescence reflected from an (n-1)-th narrow-band-pass filter is allowed to enter an n-th narrow-band-pass filter, and an intensity Pn of fluorescence transmitted through the n-th narrow-band-pass filter is detected by an n-th light-receiving portion, and

wherein a relative ratio or a difference between the intensities P1, P2,...,Pn of the fluorescence detected respectively by the n light-receiving portions is determined to detect a wavelength width of a spectrum of the fluorescence.

Application Serial No: 10/518,136

Responsive to the Advisory Action of 8/6/2008 and the final Office Action of 4/7/2008

4. (Cancelled)

5. (Withdrawn) A fluorometer for detecting intensity of fluorescence generated from a substance that is excited by light emitted from a light source, comprising:

n (n is an integer of not less than 2) narrow-band reflection-type notch filters for reflecting light in different limited wavelength regions of the fluorescence, and

n light-receiving portions having one-to-one correspondence with the n narrow-band reflection-type notch filters,

wherein an intensity P1 of fluorescence reflected from a first narrow-band reflection-type notch filter is detected by a first light-receiving portion, and

wherein fluorescence transmitted through an (n-1)-th narrow-band reflection-type notch filter is allowed to enter an n-th narrow-band reflection-type notch filter, and an intensity Pn of fluorescence reflected from the n-th narrow-band reflection-type notch filter is detected by an n-th light-receiving portion.

6. (Withdrawn) The fluorometer according to claim 5, wherein the narrow-band reflection-type notch filter comprises a pair of glass substrates and a photopolymer arranged between the pair of glass substrates, and a periodic change in refractive index of the photopolymer occurs in its thickness direction.

7. (Withdrawn) The fluorometer according to claim 5, wherein a relative ratio or a difference between the intensities P1, P2, ..., Pn of the fluorescence detected respectively by the n light-receiving portions is determined.

Claims 8-11. (Cancelled)

12. (Currently Amended) The ~~fluorometer system~~ according to claim 3, wherein the light source is a light-emitting diode.

Application Serial No: 10/518,136

Responsive to the Advisory Action of 8/6/2008 and the final Office Action of 4/7/2008

13. (Currently Amended) The ~~fluorometer-system~~ according to claim 3, wherein the light source is a wavelength-variable semiconductor laser.

14. (Currently Amended) The ~~fluorometer-system~~ according to claim 3, wherein a rare-earth element is added to the substance.

15. (Currently Amended) The ~~fluorometer-system~~ according to claim 3, wherein a wavelength width of a spectrum of the fluorescence generated from the substance is detected by comparing the detected intensities P1, P2, ..., Pn of the fluorescence.

16. (Withdrawn) The fluorometer according to claim 5, wherein the light source is a light-emitting diode.

17. (Withdrawn) The fluorometer according to claim 5, wherein the light source is a wavelength-variable semiconductor laser.

18. (Withdrawn) The fluorometer according to claim 5, wherein a rare-earth element is added to the substance.

19. (Withdrawn) The fluorometer according to claim 5, wherein a wavelength width of a spectrum of the fluorescence generated from the substance is detected by comparing the detected intensities P1, P2, ..., Pn of the fluorescence.

20. (Currently Amended) The ~~fluorometer-system~~ according to claim 3, wherein differences between the wavelength width of the spectrum of the fluorescence are distinguished with one or more substances with different fluorescence spectra.